

ClimaTemp
Portables

ClimaTemp Revolt 5000 LGR Dehumidifier

THE WORKHORSE OF LGR DEHUMIDIFIERS

THE REVOLT LGR 5000 IS A PROVEN WORKHORSE WITH A MARKET LEADING 130PINTS/DAY OF MOISTURE AND 230 PINTS/DAY AT SATURATION.

THIS DEHUMIDIFIER IS PERFECT FOR ANY MOISTURE REMOVAL PROJECT FROM REMEDIATION JOBS, FLOODING APPLICATIONS OR HIGH HUMIDITY ENVIRONMENTS. THE REVOLT COMBINES PROVEN DESIGN WITH PROFESSIONAL PERFORMANCE AND PORTABILITY. THE ROTOMOLDED POLYETHYLENE HOUSING IS DENT AND SCRATCH RESISTANT AND OFFERS SUPERIOR DURABILITY. UNITS CAN BE STACKED UP TO TWO UNITS HIGH FOR STORAGE. A RIGID HANDLE AND SEMI-PNEUMATIC WHEELS ENSURE EASY TRANSPORT AND MANEUVERABILITY.



REVOLT 5000 LGR SPECIFICATIONS

VOLTAGE & HERTZ	AC 115V / 60Hz
POWER CONSUMPTION & CURRENT	945W/8.3A @80°F, 60% RH 1140W/10.6A @86°F, 80% RH
REFRIGERANT CHARGE	R410A/26.8oz (760g)
DEHUMIDIFY CAPACITY	130PINTS/DAY @80°F, 60% RH 200PINTS/DAY @86°F, 80% RH 230PINTS/DAY @SATURATION
MAXIMUM DESIGN PRESSURE	HIGH SIDE: 522PSIG (3.6MPA) LOW SIDE: 240PSIG (1.65MPA)
COMPRESSOR INPUT	RLA: 9.1A LRA:50.5A
FAN MOTOR POWER	0.187HP



877-823-2722
www.AmericanPortableAir.com